



Channel - Standard

Depth in Inches 'A'	Weight Per Foot in Lbs	Flange Width in Inches 'B'	Web Thickness in Inches 'C'	Weight in Lbs			
				20'	40'	Galv Per Foot	Galv 20'
3	3.5	1.372	.135	70	140	3.68	74
	4.1	1.410	.170	82	164	4.31	87
	5.0	1.498	.258	100	200	5.25	105
	6.0	1.596	.356	120	240	6.30	126
4	4.5	1.570	.140	90	180	4.73	95
	5.4	1.584	.184	108	216	5.67	114
	6.25	1.647	.247	125	250	6.56	132
	7.25	1.721	.321	145	290	7.61	153
5	6.7	1.750	.190	134	268	7.04	141
	9.0	1.885	.325	180	360	9.45	189
6	8.2	1.920	.200	164	328	8.61	173
	10.5	2.034	.314	210	420	11.03	221
	13.0	2.157	.437	260	520	13.65	273
7	9.8	2.090	.210	196	392	10.29	206
	12.25	2.194	.314	245	490	12.86	258
	14.75	2.299	.419	295	590	15.49	310
8	11.5	2.260	.220	230	460	12.08	242
	13.75	2.343	.303	275	550	14.44	289
	18.75	2.527	.487	375	750	19.69	394
9	13.4	2.433	.233	268	536	14.07	282
	15.0	2.485	.285	300	600	15.75	315
	20.0	2.648	.448	400	800	21.00	420
10	15.3	2.600	.240	306	612	16.07	322
	20.0	2.739	.379	400	800	21.00	420
	25.0	2.886	.526	500	1,000	26.25	525
	30.0	3.033	.673	600	1,200	31.50	630
12	20.7	2.942	.282	414	828	21.74	435
	25.0	3.047	.387	500	1,000	26.25	525
	30.0	3.170	.510	600	1,200	31.50	630
15	33.9	3.400	.400	678	1,356	35.60	712
	40.0	3.520	.520	800	1,600	42.00	840
	50.0	3.716	.716	1,000	2,000	52.50	1,050

Channel - Junior

Depth in Inches 'A'	Weight Per Foot in Lbs	Flange Width in Inches 'B'	Web Thickness in Inches 'C'	Weight in Lbs			
				20'	40'	Galv Per Foot	Galv 20'
8	8.5	1.875	.180	170	340	8.93	179
10	6.5	1.127	.152	130	260	6.83	137
	8.4	1.500	.170	168	336	8.82	177
12	10.6	1.500	.190	212	424	11.13	223



Channel - Miscellaneous

Depth in Inches 'A'	Weight Per Foot in Lbs	Flange Width in Inches 'B'	Web Thickness in Inches 'C'	Weight in Lbs			
				20'	40'	Galv Per Foot	Galv 20'
3	7.1	1.938	.312	142	284	7.46	150
4	13.8	2.500	.500	276	552	14.49	290
6	12.0	2.497	.310	240	480	12.60	252
	15.1	2.941	.316	302	604	15.86	318
	15.3	3.500	.340	306	612	16.07	322
	16.3	3.000	.375	326	652	17.12	343
	18.0	3.504	.379	360	720	18.90	378
7	19.1	3.452	.352	382	764	20.06	402
	22.7	3.603	.503	454	908	23.84	477
8	18.7	2.978	.353	374	748	19.64	393
	20.0	3.025	.400	400	800	21.00	420
	21.4	3.450	.375	428	856	22.47	450
	22.8	3.502	.427	456	912	23.94	479
9	23.9	3.450	.400	478	956	25.10	502
	25.4	3.500	.450	508	1,016	26.67	534
10	22.0	3.315	.312	440	880	23.10	462
	25.0	3.405	.380	500	1,000	26.25	525
	28.5	3.950	.425	570	1,140	29.93	599
	33.6	4.100	.575	672	1,344	35.28	706
	41.1	4.321	.796	822	1,644	43.16	864
12	31.0	3.670	.370	620	1,240	32.55	651
	35.0	3.767	.467	700	1,400	36.75	735
	40.0	3.890	.590	800	1,600	42.00	840
	45.0	4.012	.712	900	1,800	47.25	945
	50.0	4.135	.835	1,000	2,000	52.50	1,050
13	31.8	4.000	.375	636	1,272	33.39	668
	35.0	4.072	.447	700	1,400	36.75	735
	40.0	4.185	.560	800	1,600	42.00	840
	50.0	4.412	.787	1,000	2,000	52.50	1,050
18	42.7	3.950	.450	854	1,708	44.84	897
	45.8	4.000	.500	916	1,832	48.09	962
	51.9	4.100	.600	1,038	2,076	54.50	1,090
	58.0	4.200	.700	1,160	2,320	60.90	1,218

Channel - Bar

Depth in Inches 'A'	Weight Per Foot in Lbs	Flange Width in Inches 'B'	Web Thickness in Inches 'C'	Weight in Lbs		
				20'	Galv Per Foot	Galv 20'
1	.84	1/2	1/8	17	.88	18
1 1/4	1.00	1/2	1/8	20	1.05	21
1 1/2	1.12	1/2	1/8	23	1.18	24
	1.17	3/4	1/8	24	1.23	25
2	1.43	1/2	1/8	29	1.50	31
	1.59	1	1/8	32	1.67	34
	2.32	1	3/16	47	2.70	54